


Roxtec Drawings: S103379, S103383 Instance options: Size (6, 8) Combination (x1, x2, x3, x4) Material options: Galvanized steel, Acid-proof stainless steel

GH frames

Size	Material	Title	Art. No	Weight [kg]	Ext. dim. WxHxD [mm]	Aperture WxH [mm]
6	GALV	GH 6x1 GALV	SGH000007892	4,7	252,5 x 350 x 60	148 x 242
		GH 6x2 GALV	SGH000007893	7,3	383 x 350 x 60	278 x 242
		GH 6x3 GALV	SGH000008108	9,3	513,5 x 350 x 60	409 x 242
		GH 6x4 GALV	SGH000009586	13,2	644 x 350 x 60	539 x 242
ASIS16	ASIS16	GH 6x1 ASIS16	SGH000008281	4,8	252,5 x 350 x 60	148 x 242
		GH 6x2 ASIS16	SGH000008179	7,3	383 x 350 x 60	278 x 242
		GH 6x3 ASIS16	SGH000008292	9,3	513,5 x 350 x 60	409 x 242
		GH 6x4 ASIS16	SGH000007894	12,4	644 x 350 x 60	539 x 242
8	GALV	GH 8x1 GALV	SGH000002115	5,3	252,5 x 410 x 60	148 x 302
		GH 8x2 GALV	SGH000008067	8,3	383 x 410 x 60	278 x 302
		GH 8x3 GALV	SGH000008049	10,8	513,5 x 410 x 60	409 x 302
		GH 8x4 GALV	SGH000008107	13,3	644 x 410 x 60	539 x 302
ASIS16	ASIS16	GH 8x1 ASIS16	SGH000008395	5,3	252,5 x 410 x 60	148 x 302
		GH 8x2 ASIS16	SGH000008124	8,3	383 x 410 x 60	278 x 302
		GH 8x3 ASIS16	SGH000008034	11,1	513,5 x 410 x 60	409 x 302
		GH 8x4 ASIS16	SGH000008380	13,8	644 x 410 x 60	539 x 302




Fire Weather, rodents/insects, dust Other sizes available upon request

Roxtec Drawings: S1032979, S1032126 Instance options: Size (6, 8) Combination (x1, x2, x3, x4) Material options: Galvanized steel, Acid-proof stainless steel

GH BG™ frames

Size	Material	Title	Art. No	Weight [kg]	Ext. dim. WxHxD [mm]	Aperture WxH [mm]
6	GALV	GH BG 6x1 GALV	116604	4,9	252,5 x 350 x 60	148 x 242
		GH BG 6x2 GALV	110003	7,9	383 x 350 x 60	278 x 242
		GH BG 6x3 GALV	110015	10,0	513,5 x 350 x 60	409 x 242
		GH BG 6x4 GALV	110046	12,46	644 x 350 x 60	539 x 242
ASIS16	ASIS16	GH BG 6x1 ASIS16	122511	5,0	252,5 x 350 x 60	148 x 242
		GH BG 6x2 ASIS16	122512	7,7	383 x 350 x 60	278 x 242
		GH BG 6x3 ASIS16	110477	10,2	513,5 x 350 x 60	409 x 242
		GH BG 6x4 ASIS16	122513	12,46	644 x 350 x 60	539 x 242
8	GALV	GH BG 8x1 GALV	117224	5,9	252,5 x 410 x 60	148 x 302
		GH BG 8x2 GALV	116088	8,9	383 x 410 x 60	278 x 302
		GH BG 8x3 GALV	110838	11,3	513,5 x 410 x 60	409 x 302
		GH BG 8x4 GALV	111344	14,1	644 x 410 x 60	539 x 302
ASIS16	ASIS16	GH BG 8x1 ASIS16	122533	5,9	252,5 x 410 x 60	148 x 302
		GH BG 8x2 ASIS16	122539	8,7	383 x 410 x 60	278 x 302
		GH BG 8x3 ASIS16	122540	11,6	513,5 x 410 x 60	409 x 302
		GH BG 8x4 ASIS16	122541	14,1	644 x 410 x 60	539 x 302




EMC Grounding & bonding Weather, rodents/insects, dust Other sizes available upon request

Roxtec Drawings: S1032569, S1032561 Instance options: Size (6, 8) Combination (x1, x2, x3, x4) Material options: Galvanized steel, Acid-proof stainless steel

GH FL100 frames

Size	Material	Title	Art. No	Weight [kg]	Ext. dim. WxHxD [mm]	Aperture WxH [mm]
6	GALV	GH FL 6x1 GALV	122156	7,2	332,5 x 430 x 60	148 x 242
		GH FL 6x2 GALV	122159	10,2	463 x 430 x 60	278 x 242
		GH FL 6x3 GALV	122160	13,2	593,5 x 430 x 60	409 x 242
		GH FL 6x4 GALV	122161	16,2	724 x 430 x 60	539 x 242
ASIS16	ASIS16	GH FL 6x1 ASIS16	122559	7,4	332,5 x 430 x 60	148 x 242
		GH FL 6x2 ASIS16	122560	10,4	463 x 430 x 60	278 x 242
		GH FL 6x3 ASIS16	122560	13,2	593,5 x 430 x 60	409 x 242
		GH FL 6x4 ASIS16	122561	16,2	724 x 430 x 60	539 x 242
8	GALV	GH FL 8x1 GALV	122181	8,1	332,5 x 490 x 60	148 x 302
		GH FL 8x2 GALV	117391	11,4	463 x 490 x 60	278 x 302
		GH FL 8x3 GALV	122182	14,7	593,5 x 490 x 60	409 x 302
		GH FL 8x4 GALV	122183	17,9	724 x 490 x 60	539 x 302
ASIS16	ASIS16	GH FL 8x1 ASIS16	122599	8,3	332,5 x 490 x 60	148 x 302
		GH FL 8x2 ASIS16	117796	11,6	463 x 490 x 60	278 x 302
		GH FL 8x3 ASIS16	118625	15,0	593,5 x 490 x 60	409 x 302
		GH FL 8x4 ASIS16	117225	18,3	724 x 490 x 60	539 x 302




Fire EMC Grounding & bonding Weather, rodents/insects, dust Other sizes available upon request

Roxtec Drawings: S1032566 Instance options: Size (75, 100, 125, 150, 200) Combination (x1, x2, x3, x4) Material options: Galvanized steel, Acid-proof stainless steel

GH BG™ FL100 frames

Size	Material	Title	Art. No	Weight [kg]	Ext. dim. WxHxD [mm]	Aperture WxH [mm]
6	GALV	GH BG FL 100 GALV	122388	7,4	332,5 x 430 x 60	148 x 242
		GH BG FL 100 GALV	122389	10,8	463 x 430 x 60	278 x 242
		GH BG FL 100 GALV	122390	13,9	593,5 x 430 x 60	409 x 242
		GH BG FL 100 GALV	122391	16,9	724 x 430 x 60	539 x 242
ASIS16	ASIS16	GH BG FL 100 ASIS16	122392	7,5	332,5 x 430 x 60	148 x 242
		GH BG FL 100 ASIS16	122393	10,9	463 x 430 x 60	278 x 242
		GH BG FL 100 ASIS16	122394	13,9	593,5 x 430 x 60	409 x 242
		GH BG FL 100 ASIS16	122395	16,9	724 x 430 x 60	539 x 242
8	GALV	GH BG FL 100 GALV	122419	8,3	332,5 x 490 x 60	148 x 302
		GH BG FL 100 GALV	122420	11,9	463 x 490 x 60	278 x 302
		GH BG FL 100 GALV	118214	15,0	593,5 x 490 x 60	409 x 302
		GH BG FL 100 GALV	122422	18,3	724 x 490 x 60	539 x 302
ASIS16	ASIS16	GH BG FL 100 ASIS16	122399	8,5	332,5 x 490 x 60	148 x 302
		GH BG FL 100 ASIS16	122398	12,5	463 x 490 x 60	278 x 302
		GH BG FL 100 ASIS16	122399	16,1	593,5 x 490 x 60	409 x 302
		GH BG FL 100 ASIS16	122398	18,1	724 x 490 x 60	539 x 302




Fire EMC Grounding & bonding Weather, rodents/insects, dust Other sizes available upon request

Roxtec Drawings: S1005511, S1005512, S1005506 Instance options: Size (75, 100, 125, 150, 200) Material options: Roxylon EPDM rubber, Acid-proof stainless steel

R frames

Title	Art. No	Weight [kg]	Aperture [Ø mm]
R 75 AISI316	R000000751021	0,5	75 - 77
R 100 AISI316	R000001001021	0,8	100 - 102
R 125 AISI316	R000001251021	1,1	125 - 127
R 150 AISI316	R000001501021	1,6	150 - 152
R 200 AISI316	R000002001021	2,6	200 - 202




Fire Weather, rodents/insects, dust Other sizes available upon request

Roxtec Drawings: S1005507, S1005509, S1005510, S1006570, S1007759, S1006598 Instance options: Size (25, 50, 75, 100, 125, 150, 175, 200, 225, 250) Material options: Roxylon EPDM rubber, Acid-proof stainless steel

RS seals

Title	Art. No	Weight [kg]	Aperture [Ø mm]	Cable Ø [mm]
RS 25 AISI316	RS00100251023	0,04	25 - 26	3,8 - 4,1
RS 50 AISI316	RS00100501023	0,32	50 - 52	6 - 8
RS 75 AISI316	RS00100751023	0,6	75 - 77	24 - 54
RS 100 AISI316 WOC	RS00001001023	0,8	100 - 102	48 - 70
RS 125 AISI316 WOC	RS00001251023	1,2	125 - 127	66 - 86
RS 150 AISI316 WOC	RS00001501023	1,6	150 - 152	93 - 119
RS 175 AISI316 WOC	RS00175750021	2,3	175 - 177	119 - 145
RS 200 AISI316 WOC	RS00200750021	2,7	200 - 202	138 - 170
RS 225 AISI316 WOC	RS00002250021	3,2	225 - 228	151 - 181
RS 250 AISI316 WOC	RS00002500021	3,3	250 - 253	176 - 206




Fire Weather, rodents/insects, dust Other sizes available upon request

Roxtec Drawings: S103925 Instance options: Size (150, 200) Material options: Roxylon EPDM rubber, Acid-proof stainless steel

H3 seals

Title	Art. No	Weight [kg]	Aperture [Ø mm]	Cable Ø [mm]
H3-150	122905	2,8	150 - 152	3 x 24 - 54
H3-200	122909	4,9	200 - 202	3 x 48 - 70




Fire Weather, rodents/insects, dust Other sizes available upon request

Roxtec Drawings: S153134 Instance options: Size (100, 150, 200) Wall depth (100, >100) Material options: ABS

Knock-out sleeves

Wall depth	Title	Art. No	Weight [kg]	For sealing [Ø mm]
100	KOS 100/100 D=100	184063	0,3	100
	KOS 150/150 D=100	184065	0,4	150
	KOS 200/200 D=100	184067	0,6	200
>100	KOS 100/116 D=150	184064	0,4	100
	KOS 150/160 D=150	184066	0,6	150
	KOS 200/200 D=150	184068	0,8	200




0.3 bar 0.3 bar IP 68 Weather, rodents/insects, dust Other sizes available upon request

Roxtec Drawings: S103547 Instance options: Size (100, 150, 200) Material options: Roxylon EPDM rubber, Acid-proof stainless steel

R UG frames

Title	Art. No	Weight [kg]	Aperture [Ø mm]
R 100 UG	156872	0,8	100 - 102
R 150 UG	108693	1,9	150 - 152
R 200 UG	108698	3,1	200 - 202




0.3 bar 0.3 bar IP 68 Weather, rodents/insects, dust Other sizes available upon request

Roxtec Drawings: S1511690, S1522905 Instance options: Size (75, 100(24-53), 100, 125, 135, 150, 165, 200, 225, 250) Material options: Roxylon EPDM rubber, Acid-proof stainless steel

RS UG seals

Title	Art. No	Weight [kg]	Aperture [Ø mm]	Cable Ø [mm]
RS 75 UG	186247	0,7	75 - 80	9 - 33
RS 100 24-53 UG	186250	1,0	100 - 105	24 - 53
RS 100 UG WOC	167265	1,0	100 - 105	39 - 63
RS 125 UG WOC	167639	1,4	125 - 130	55 - 88
RS 135 UG WOC	167266	1,6	135 - 140	65 - 98
RS 150 UG WOC	167246	1,9	150 - 155	80 - 113
RS 185 UG WOC	167258	2,3	185 - 190	114 - 148
RS 200 UG WOC	178151	2,5	200 - 205	130 - 163
RS 225 UG WOC	178166	3,4	225 - 230	148 - 179
RS 250 UG WOC	178178	3,9	250 - 255	171 - 204




0.3 bar 0.3 bar IP 68 Weather, rodents/insects, dust Other sizes available upon request

Roxtec Drawings: S1501351, S1033803 Instance options: Size (150, 200) Material options: Roxylon EPDM rubber, Acid-proof stainless steel

H3 UG seals

Title	Art. No	Weight [kg]	Aperture [Ø mm]	Cable Ø [mm]
H3-150 UG	151561	2,5	150 - 155	3 x 24 - 52
H3-200 UG	117842	4,3	200 - 205	3 x 48 - 68




0.3 bar 0.3 bar IP 68 Weather, rodents/insects, dust Other sizes available upon request

Roxtec Drawings: S1539804, S1539766 Instance options: Size (150, 200) Material options: Roxylon EPDM rubber, Acid-proof stainless steel

H4 UG seals

Title	Art. No	Weight [kg]	Aperture [Ø mm]	Cable Ø [mm]
H4-150 UG	192261	2,5	150 - 155	3 x 24 - 53, (10 - 23,5)
H4-200 UG	192082	4,3	200 - 205	3 x 39 - 68, (10 - 23,5)



0.3 bar 0.3 bar IP 68 Weather, rodents/insects, dust Other sizes available upon request